

更に上のクオリティ
更に上のサービス!

問題集

ITEXAMPASS

<https://www.itexampass.jp>



1年で無料進級することに提供する

Exam : **1Z0-400**

Title : Oracle Communications
Session Border Controller

Version : Demo

1. When the nat-traversal parameter is set to "always", the Session Border Controller compares the _____ and the Layer-3 source address to determine whether the endpoint is behind a NAT device and further compares the _____ to the Layer-3 source address to determine whether to add the registration to its registration cache.

- A. SIP Proxy IP address; SIP Registrar address
- B. Sent-by of the bottom most via header; host address of the Contact URI
- C. From address; host address of the Contact URI
- D. Host address of the Contact URI; from address
- E. Sent-by of the top most via header; host address of the Contact URI

Answer: B, D

2. Which statement about passwords on the Net-Net 4500 is FALSE?

- A. The User and Superuser modes are password protected.
- B. Passwords are stored in NVRAM.
- C. You do not need User and Superuser mode passwords when accessing the ACLI using SSH.
- D. Passwords cannot be seen in the output from the running configuration.
- E. The default user mode password is "acme".

Answer: E

Explanation:

Reference: https://docs.oracle.com/cd/E50366_01/doc/sbc_scx640_adminsecurity.pdf

3. By default, the Session Border Controller's FTP, ICMP, SNMP, and Telnet services cannot be accessed via the media interfaces. In order to enable these services, the Session Border Controller includes four fields that enable administrative traffic over the media interfaces. These four fields are collectively known as the "HIP".

What does the acronym HIP stand for?

- A. HostinPath
- B. Host Internet Protocol
- C. Host Interface Priority
- D. Healthy Interface Port
- E. Health Indicator Protocol

Answer: B

4. The _____ field allows you to set the health score at which the standby peer in a high availability (HA) scenario will switch over to the active state without waiting for any configured timers to expire.

- A. Emergency-threshold
- B. Health-threshold
- C. Active-threshold
- D. Switchover-threshold
- E. Ha-threshold

Answer: C

5. When configuring the Net-Net 4500, _____ SIP interface(s) is/are allowed per realm, and _____ SIP port (s) is/are allowed for a SIP interface.

A. Multiple; multiple

B. One; 1024

C. Multiple; 999

D. One; multiple

E. One; one

Answer: D