

更に上のクオリティ
更に上のサービス!

問題集

ITEXAMPASS

<https://www.itexampass.jp>



1年で無料進級することに提供する

Exam : **JN0-363**

Title : Service Provider Routing
and Switching, Specialist
(JNCIS-SP)

Version : DEMO

1.Which BGP attribute is used to detect routing loops?

- A. AS path
- B. MED
- C. local preference
- D. next hop

Answer: A

2.What is the correct order of BGP attributes for active route selection?

- A. next hop -> local preference -> AS path -> MED -> origin
- B. next hop -> AS path -> local preference -> origin -> MED
- C. next hop -> local preference -> AS path -> origin -> MED
- D. next hop -> origin -> local preference -> AS path -> MED

Answer: C

3.Which new field is added to an IPv6 header as compared to IPv4?

- A. version
- B. checksum
- C. fragment offset
- D. flow label

Answer: D

4.How does a Junos device learn about MAC addresses when it is first connected to an Ethernet LAN?

- A. The device sends out a network broadcast message asking for all devices and MAC addresses on the network and stores this information in addition to the interface from which the response was received.
- B. The device learns the destination MAC addresses from traffic in the network and stores this MAC address in addition to the interface from which the traffic was received.
- C. The device learns the source MAC addresses from traffic in the network and stores this MAC address in addition to the interface from which the traffic was received.
- D. The device sends out a network multicast message asking for all devices and MAC addresses on the network and stores this information in addition to the interface from which the response was received.

Answer: C

5.Which LSA type does an OSPF ABR use to advertise external routes generated by an NSSAASBR into the backbone?

- A. Type 5
- B. Type 7
- C. Type 3
- D. Type 1

Answer: B